

650V 6A Silicon Carbide Schottky Diode

AKC65D006GHH

Features:



- Zero Reverse Recovery Current / Forward Recovery Voltage
- High Non-repetitive Peak Forward Surge Current (I_{FSM})
- Low Forward Voltage (V_F)
- Low Leakage Current (I_R)
- RoHS Compliant (Note 1)
- Halogen-free (Note 1)

Applications:

- Solar Inverters
- Industrial Power Supplies
- High Voltage DC/DC Converters
- Switch Mode Power Supplies
- Uninterruptible Power Supplies

Key Performance Parameters:

Parameter	Value	Unit
V_{RRM}	650	V
I_F	6	A
Q_C	18	nC
P_D	50	W
T_J	175	°C



Ordering Information:

Ordering Code	Package Type	Marking Code	Form	Packing
AKC65D006GHH	DFN 5*6	C65D006GHH	Tape reel	5000 pcs

Thermal Characteristics

Symbol	Parameter	Value	Units
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case, Steady-State	3	°C/W

Maximum Ratings ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter		Value	Units
V_{RRM}	Repetitive Peak Reverse Voltage		650	V
I_F	Continuous Forward Current	$T_C = 25\text{ }^\circ\text{C}$	21	A
		$T_C = 125\text{ }^\circ\text{C}$	9	A
		$T_C = 149\text{ }^\circ\text{C}$	6	A
I_{FRM}	Repetitive Peak Forward Surge Current	$T_C = 25\text{ }^\circ\text{C}$, $t_p = 10\text{ ms}$, Half Sine Wave	20	A
		$T_C = 110\text{ }^\circ\text{C}$, $t_p = 10\text{ ms}$, Half Sine Wave	14	A
I_{FSM}	Non-repetitive Peak Forward Surge Current	$T_C = 25\text{ }^\circ\text{C}$, $t_p = 10\text{ ms}$, Half Sine Wave	40	A
		$T_C = 110\text{ }^\circ\text{C}$, $t_p = 10\text{ ms}$, Half Sine Wave	35	A
$I_{F,max}$	Non-repetitive Peak Forward Surge Current	$T_C = 25\text{ }^\circ\text{C}$, $t_p = 10\text{ }\mu\text{s}$, Pulse	370	A
		$T_C = 110\text{ }^\circ\text{C}$, $t_p = 10\text{ }\mu\text{s}$, Pulse	315	A
P_D	Power Dissipation	$T_C = 25\text{ }^\circ\text{C}$	50	W
		$T_C = 110\text{ }^\circ\text{C}$	21	W
T_J	Operating Junction Temperature		175	$^\circ\text{C}$
T_{STG}	Storage Temperature		-55~175	$^\circ\text{C}$


Electrical Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
V_{BR}	Reverse Breakdown Voltage	$I_R = 100 \mu\text{A}$	650	-	-	V
V_F	Forward Voltage	$I_F = 6 \text{ A}, T_J = 25^\circ\text{C}$	-	1.35	1.50	V
		$I_F = 6 \text{ A}, T_J = 175^\circ\text{C}$	-	1.75	1.90	V
I_R	Reverse Leakage Current	$V_R = 650 \text{ V}, T_J = 25^\circ\text{C}$	-	10	50	μA
		$V_R = 650 \text{ V}, T_J = 175^\circ\text{C}$	-	20	150	μA
Q_C	Total Capacitive Charge	$V_R = 400 \text{ V},$ $Q_C = \int_0^{V_R} C(V_R) dV(V_R)$	-	18	-	nC
C	Total Capacitance	$V_R = 0 \text{ V}, f = 100 \text{ kHz}$ $T_J = 25^\circ\text{C}$	-	300	-	pF
		$V_R = 400 \text{ V}, f = 100 \text{ kHz}$ $T_J = 25^\circ\text{C}$	-	28	-	pF
E_C	Capacitance Stored Energy	$V_R = 400 \text{ V}$	-	4.6	-	μJ

Notes:

1. Contact ALKAIDSEMI sales for detail information

Electrical Characteristics Diagrams






Figure 7: I_{FSM} vs. Pulse duration




Figure 8: Current De-rating






Figure 9: Normalized Maximum Transient Thermal Impedance

Package Outlines

DFN5x6 PACKAGE OUTLINE



RECOMMENDED LAND PATTERN



UNIT: mm

	MIN	NOM	MAX
A	0.90	1.00	1.10
b	0.25	0.35	0.50
c	0.10	0.20	0.30
D	4.80	5.00	5.30
D1	4.90	5.10	5.50
D2	3.92	4.02	4.20
E	5.65	5.75	5.85
E1	5.90	6.05	6.20
E2	3.325	3.525	3.775
E3	0.80	0.90	1.00
e		1.27	
L	0.40	0.55	0.70
L1		0.65	
L2	0.00		0.15
K	1.00	1.30	1.50

Marking Information



Note:

C65D006GHH = Product Name Code

XXXXXXX = Date code

Contact ALKAIDSEMI sales for detail information

Revision History

Revision	Release Date	Remark
Rev.1.5	2022-07-13	

Disclaimer

The information given in this document describes the independent performance of the product, but similar performance is not guaranteed under other working conditions, and cannot be guaranteed when installed with other products or equipment. To achieve the required performance of the product in actual scenarios, the customer should conduct a complete application test to assess the functionality of the product.

Alkaidsemi assumes no responsibility for equipment failures result from using products at values that exceed the ratings, operating conditions, or other parameters listed in the product specifications.

The product described in this specification is not applicable for aerospace or other applications which requires high reliability. Customers using or selling these products for use in medical, life-saving, or life-sustaining applications do so at their own risk and agree to fully indemnify.

Due to product or technical improvements, the information described or contained herein may be changed without prior notice.