

60V 3.6mohm N-channel SGT MOSFET AKG6N036DM

Description:

This N channel SGT MOSFET has been designed to low on-state resistance and superior E_{AS} performance, especially for BMS and Motor driving applications.

Features:



- Low $R_{DS(ON)}$
- 100% UIS Tested
- RoHS compliant ^(Note 1)
- Halogen-free ^(Note 1)

Applications:

- Battery Management System
- Motor Drivers
- DC-DC Converter

Key Performance Parameters:

Parameter	Value	Unit
V_{DS}	60	V
$R_{DS(ON), max} @V_{GS} = 10V$	3.6	m Ω
I_D	120	A



Ordering Information:

Ordering Code	Package Type	Marking Code	Form	Packing
AKG6N036DM	TO-263	G6N036DM	Tape Reel	1000PCS

Notes:

1. Contact ALKAIDSEMI sales for detail information

Maximum Ratings (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Value	Units
V _{DS}	Drain-Source Voltage	60	V
I _D	Drain Current - Continuous (T _C = 25°C) ^(Note 1)	180	A
	Drain Current - Continuous (T _C = 25°C) ^(Note 2)	120	A
	Drain Current - Continuous (T _C = 100°C)	113	A
I _{DM}	Drain Current - Pulsed ^(Note 3)	460	A
V _{GS}	Gate-Source Voltage	± 20	V
E _{AS}	Single Pulsed Avalanche Energy ^(Note 4)	338	mJ
P _D	Power Dissipation (T _C = 25°C)	208	W
T _J , T _{STG}	Operating and Storage Temperature Range	-55 to +150	°C

Thermal Characteristics

Symbol	Parameter	Value	Units
R _{θJC}	Thermal Resistance, Junction-to-Case, Steady-State	0.6	°C/W
R _{θJA}	Thermal Resistance, Junction-to-Ambient, Steady State ^(Note 5)	60	°C/W

Notes:

1. The max drain current rating is silicon limited
2. The max drain current rating is package limited
3. Repetitive Rating: Pulse width limited by maximum junction temperature
4. L = 0.5 mH, V_{DD} = 30V, I_{AS} = 37 A, R_G = 25 Ω, Starting T_J = 25 °C
5. Mount on minimum PCB layout

Electrical Characteristics ($T_J = 25^\circ\text{C}$ unless otherwise noted)						
Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_D = 250\ \mu\text{A}$	60			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 60\text{ V}, V_{GS} = 0\text{ V}$			1	μA
I_{GSS}	Gate Leakage Current	$V_{GS} = \pm 20\text{ V}, V_{DS} = 0\text{ V}$			± 100	nA
$V_{GS(TH)}$	Gate Threshold voltage	$V_{DS} = V_{GS}, I_D = 250\ \mu\text{A}$	2	3	4	V
$R_{DS(ON)}$	Drain-Source on-state resistance	$V_{GS} = 10\text{ V}, I_D = 40\text{ A}$		3.1	3.6	m Ω
Dynamic Characteristics						
C_{ISS}	Input Capacitance	$V_{DS} = 30\text{ V}, V_{GS} = 0\text{ V},$ $F = 1\text{ MHz}$		6579		pF
C_{OSS}	Output Capacitance			1326		pF
C_{RSS}	Reverse Transfer Capacitance			112		pF
R_G	Gate Resistance	$F = 1\text{ MHz}$		1.4		Ω
Switching Characteristics						
$T_{D(ON)}$	Turn On Delay Time	$V_{DD} = 30\text{ V}, R_L = 0.75\ \Omega,$ $V_{GS} = 10\text{ V}, R_G = 4.7\ \Omega$		29		nS
T_R	Rise Time			50.5		nS
$T_{D(OFF)}$	Turn Off Delay Time			76.5		nS
T_F	Fall Time			36.5		nS
Q_G	Total Gate Charge	$V_{DD} = 30\text{ V}, I_D = 40\text{ A},$ $V_{GS} = 10\text{ V}$		103		nC
Q_{GS}	Gate-Source Charge			27		nC
Q_{GD}	Gate-Drain Charge			25.5		nC
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Body-Diode Forward Current			120		A
I_{SM}	Maximum Pulsed Body-Diode Forward Current ^(NOTE 2)			460		A
V_{SD}	Diode Forward Voltage	$V_{GS} = 0\text{ V}, I_S = 40\text{ A}$		0.8	1.2	V
T_{RR}	Reverse recovery time	$V_{DD} = 30\text{ V}, I_D = 40\text{ A},$ $di/dt = 100\text{ A}/\mu\text{S}$		60		nS
Q_{RR}	Reverse recovery charge			93		nC
I_{RRM}	Peak Reverse Recovery Current			2.5		A

Electrical Characteristics Diagrams




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: Breakdown Voltage vs. Junction Temperature




Figure 6: Threshold Voltage vs. Junction Temperature




Figure 7: Body-Diode Characteristics




Figure 8: On-Resistance vs. Gate-Source Voltage




Figure 9: Capacitance Characteristics




Figure 10: Gate-Charge Characteristics




Figure 11: Power De-rating




Figure 12: Current De-rating




Figure 13: Normalized Maximum Transient Thermal Impedance






Figure 14: Maximum Forward Biased Safe Operating Area

Test Circuit and Waveform


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



Package Outlines




SYMBOL	INCHES		MILLIMETERS		NOTES
	MIN	MAX	MIN	MAX	
A	0.170	0.180	4.32	4.57	
A1	-	0.010	-	0.25	
b	0.028	0.037	0.71	0.94	
b2	0.045	0.055	1.15	1.40	
c	0.018	0.024	0.46	0.61	
c2	0.048	0.055	1.22	1.40	
D	0.350	0.370	8.89	9.40	
D1	0.315	0.324	8.01	8.23	
E	0.395	0.405	10.04	10.28	
E1	0.310	0.318	7.88	8.08	
e	0.100 BSC.		2.54 BSC.		
L	0.580	0.620	14.73	15.75	
L1	0.090	0.110	2.29	2.79	
L2	0.045	0.055	1.15	1.39	
L3	0.050	0.070	1.27	1.77	
θ	0°	8°	0°	8°	

Marking Information



Note:
 G6N036DM = Product Name Code
 XXXXXXXX = Date code
 Contact ALKAIDSEMI sales for detail information



Revision History

Revision	Release Date	Remark
Rev.1.0	2022/7/15	Initial Release

Disclaimer

The information given in this document describes the independent performance of the product, but similar performance is not guaranteed under other working conditions, and cannot be guaranteed when installed with other products or equipment. To achieve the required performance of the product in actual scenarios, the customer should conduct a complete application test to assess the functionality of the product.

Alkaidsemi assumes no responsibility for equipment failures result from using products at values that exceed the ratings, operating conditions, or other parameters listed in the product specifications.

The product described in this specification is not applicable for aerospace or other applications which requires high reliability. Customers using or selling these products for use in medical, life-saving, or life-sustaining applications do so at their own risk and agree to fully indemnify.

Due to product or technical improvements, the information described or contained herein may be changed without prior notice.