

## 650V 37mohm Super-Junction Power MOSFET AK3S65N370WMF

### Description:

This SJ device integrated with fast-recovery diode provides good FOM factor, EMI Friendly for customer application.

### Features:



- RoHS compliant
- Halogen-free
- 100% UIS tested
- EMI-Friendly

### Applications:

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)
- LED Light

### Key Performance Parameters:

Parameter	Value	Unit
$V_{DS}$	650	V
$R_{DS(ON)}, \text{max} @ V_{GS} = 10 \text{ V}$	37	m $\Omega$
$I_D$	65	A



### Ordering Information:

Ordering Code	Package Type	Marking Code	Form	Packing
AK3S65N370WMF	TO-247-3L	3S65N370WMF	Tube	300 per box

**Maximum Ratings** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

Symbol	Parameter	Value	Units
$V_{DS}$	Drain - Source Voltage	650	V
$I_D$	Drain Current - Continuous ( $T_C = 25^\circ\text{C}$ ) <sup>(Note 1)</sup>	65	A
	Drain Current - Continuous ( $T_C = 100^\circ\text{C}$ )	41	A
$I_{DM}$	Drain Current - Pulsed <sup>(Note 2)</sup>	220	A
$V_{GS}$	Gate - Source Voltage	$\pm 30$	V
$E_{AS}$	Single Pulsed Avalanche Energy <sup>(Note 3)</sup>	390	mJ
dv/dt	MOSFET dv/dt ruggedness	100	V/ns
	Reverse diode dv/dt	75	V/ns
$P_D$	Power Dissipation ( $T_C = 25^\circ\text{C}$ )	390	W
$T_J, T_{STG}$	Operating and Storage Temperature Range	-55 to +150	$^\circ\text{C}$

**Thermal Characteristics**

Symbol	Parameter	Value	Units
$R_{\theta JC}$	Thermal Resistance, Junction - to - Case, Steady-State	0.32	$^\circ\text{C/W}$
$R_{\theta JA}$	Thermal Resistance, Junction - to - Ambient, Steady State <sup>(Note 4)</sup>	35	$^\circ\text{C/W}$

**Notes:**

1. The max drain current rating limited by package and maximum junction temperature
2. Repetitive Rating: Pulse width limited by maximum junction temperature
3.  $L = 10.8 \text{ mH}$ ,  $V_{DD} = 150 \text{ V}$ ,  $I_{AS} = 8.5 \text{ A}$ ,  $R_g = 50 \Omega$ , Starting  $T_J = 25^\circ\text{C}$ , guarantee by design
4. Mount on minimum PCB layout

<b>Electrical Characteristics</b> ( $T_J = 25^\circ\text{C}$ unless otherwise noted)						
Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
<b>Static Characteristics</b>						
$V_{(BR)DSS}$	Drain - Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_D = 1\text{ mA}$	650			V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS} = 650\text{ V}, V_{GS} = 0\text{ V}$			10	$\mu\text{A}$
$I_{GSS}$	Gate Leakage Current	$V_{GS} = \pm 30\text{ V}, V_{DS} = 0\text{ V}$			$\pm 100$	nA
$V_{GS(th)}$	Gate Threshold voltage	$V_{DS} = V_{GS}, I_D = 250\text{ }\mu\text{A}$	3	4	5	V
$R_{DS(ON)}$	Drain - Source on - state resistance	$V_{GS} = 10\text{ V}, I_D = 32\text{ A}$		29	37	$\text{m}\Omega$
<b>Dynamic Characteristics</b>						
$C_{iss}$	Input Capacitance	$V_{DS} = 400\text{ V}, V_{GS} = 0\text{ V},$ $f = 1\text{ MHz}$		7185		pF
$C_{oss}$	Output Capacitance			103		pF
$C_{rss}$	Reverse Transfer Capacitance			16		pF
$C_{o(er)}$	Effective output capacitance, energy related	$V_{DS} = 0\dots 400\text{ V}, V_{GS} = 0\text{ V}$		207		pF
$C_{o(tr)}$	Effective output capacitance, time related	$V_{DS} = 0\dots 400\text{ V}, V_{GS} = 0\text{ V},$ $I_D = \text{constant}$		1743		pF
$R_g$	Gate Resistance	$f = 1\text{ MHz}$		3.6		$\Omega$
<b>Switching Characteristics</b>						
$t_{d(on)}$	Turn On Delay Time	$V_{DD} = 480\text{ V}, I_D = 32\text{ A}$ $V_{GS} = 10\text{ V}, R_G = 24\text{ }\Omega$		131		ns
$t_r$	Rise Time			84		ns
$t_{d(off)}$	Turn Off Delay Time			341		ns
$t_f$	Fall Time			60		ns
$Q_g$	Total Gate Charge	$V_{DD} = 400\text{ V}, I_D = 32\text{ A},$ $V_{GS} = 10\text{ V}$		160		nC
$Q_{gs}$	Gate - Source Charge			42		nC
$Q_{gd}$	Gate - Drain Charge			67		nC
<b>Drain - Source Diode Characteristics and Maximum Ratings</b>						
$I_S$	Maximum Continuous Body - Diode Forward Current				65	A
$I_{SM}$	Maximum Pulsed Body - Diode Forward Current				220	A
$V_{SD}$	Diode Forward Voltage	$V_{GS} = 0\text{ V}, I_S = 32\text{ A}$		0.9		V
$t_{rr}$	Reverse recovery time	$V_{DD} = 400\text{ V}, I_D = 32\text{ A},$ $di/dt = 100\text{ A}/\mu\text{S}$		150		ns
$Q_{rr}$	Reverse recovery charge			1.3		$\mu\text{C}$
$I_{rrm}$	Peak Reverse Recovery Current			17		A

# Electrical Characteristics Diagrams




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: Breakdown Voltage vs. Junction Temperature




Figure 6: Threshold Voltage vs. Junction Temperature




Figure 7: Body-Diode Characteristics




Figure 8: On-Resistance vs. Gate-Source Voltage




Figure 9: Capacitance Characteristics




Figure 10: Gate-Charge Characteristics




Figure 11: Power De-rating




Figure 12: Current De-rating




Figure 13: Normalized Maximum Transient Thermal Impedance






Figure 14: Maximum Forward Biased Safe Operating Area

# Test Circuit and Waveform


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms




Unclamped Inductive Switching (UIS) Test Circuit & Waveforms





Diode Recovery Test Circuit & Waveforms



Package Outlines



$\pm 0.25$  B A



SYMBOL	MIN	MAX
A	4.83	5.21
A1	2.29	2.54
A2	1.91	2.16
b'	1.07	1.28
b	1.07	1.33
b1	1.91	2.41
b2	1.91	2.16
b3	2.87	3.38
b4	2.87	3.13
c'	0.55	0.65
c	0.55	0.68
D	20.80	21.10
D1	16.25	17.65
D2	0.95	1.25
E	15.75	16.13
E1	13.10	14.15
E2	3.68	5.10
E3	1.00	1.90
E4	12.38	13.43
e	5.44 BSC	
N	3	
L	19.81	20.32
L1	4.10	4.40
P	3.51	3.65
Q	5.49	6.00
S	6.04	6.30
T	17.5 ° REF	
W	3.5 ° REF	
X	4 ° REF	



---

**Marking Information**

3S65N370WMF  
KYWWZZZ

**Note:**

3S65N370WMF = Product Name Code

KYWWZZZ = Date code

Contact ALKAIDSEMI sales for detail information

---

## Revision History

Revision	Released	Remark
Rev.1.0	2023	initial release

## Disclaimer

The information given in this document describes the independent performance of the product, but similar performance is not guaranteed under other working conditions, and cannot be guaranteed when installed with other products or equipment. To achieve the required performance of the product in actual scenarios, the customer should conduct a complete application test to assess the functionality of the product.

Alkaidsemi assumes no responsibility for equipment failures result from using products at values that exceed the ratings, operating conditions, or other parameters listed in the product specifications.

The product described in this specification is not applicable for aerospace or other applications which requires high reliability. Customers using or selling these products for use in medical, life-saving, or life-sustaining applications do so at their own risk and agree to fully indemnify.

Due to product or technical improvements, the information described or contained herein may be changed without prior